



# WOVEN WIRE SQUARE MESH

## Specifications

Hire tensile wire

Aperture (mm)	Wire (mm)	Open Area %
150.0	12.50	85
125.0	12.50	83
100.0	12.50	79
100.0	10.00	83
90.0	10.00	81
85.0	11.20	78
85.0	10.00	80
80.0	10.00	79
75.0	11.20	77
70.0	10.00	76
65.0	10.00	74
65.0	8.00	79
65.0	6.30	83
63.0	10.00	74
57.0	10.00	72
55.0	6.30	81
50.0	10.00	70
50.0	8.00	74
50.0	6.30	79
45.0	8.00	72
45.0	4.00	84
43.0	8.00	71
42.0	7.10	73
40.0	10.00	64
40.0	8.00	69
40.0	4.00	83
38.0	7.10	71
35.0	8.00	66
32.0	7.10	67
31.6	6.30	70
30.0	7.10	65
28.0	8.00	60
26.1	6.30	65
25.0	6.30	64
25.0	4.00	74

Aperture (mm)	Wire (mm)	Open Area %
24.0	8.00	56
22.7	6.30	61
22.1	7.10	57
22.0	5.60	64
21.7	6.30	60
21.0	7.10	56
20.5	5.00	65
20.2	6.30	58
20.0	4.00	69
19.2	6.30	57
19.0	5.00	63
18.4	5.60	59
17.5	6.30	60
17.3	5.00	60
16.0	6.30	52
16.0	5.60	55
16.0	5.00	58
15.5	5.60	54
15.3	5.00	56
14.8	4.00	62
14.0	5.60	51
14.0	5.00	54
13.9	6.30	47
13.9	4.00	60
13.4	5.00	53
13.0	4.00	58
13.0	2.50	70
12.5	5.00	51
12.4	3.15	63
12.0	3.15	63
11.9	5.00	50
11.8	4.00	56
11.5	5.00	49
11.2	4.00	54
11.2	3.15	61

Aperture (mm)	Wire (mm)	Open Area %
10.4	4.00	52
10.2	4.00	52
9.9	4.00	51
9.7	3.15	57
9.5	4.00	50
9.0	3.15	55
8.9	4.00	48
8.4	4.00	46
8.0	3.15	51
7.9	4.00	44
7.4	3.15	48
7.2	4.00	41
7.1	2.80	51
6.8	3.15	47
6.4	4.00	38
6.2	3.15	44
6.0	2.50	50
5.8	3.15	42
5.7	2.80	45
5.3	3.15	38
5.2	2.50	46
5.0	2.00	50
4.9	2.50	44
4.8	1.60	56
4.5	2.80	38
4.4	2.50	41
4.0	2.50	38
3.8	2.50	36
3.8	2.00	43
3.4	2.00	40
3.2	2.00	38
3.0	2.00	36
2.5	1.60	37
2.0	1.00	44